

ML750e

Ultra-compact LED projector



- **HD Ready and LED technology - Great for movies, gaming and PC-free presentations**
- **Great connectivity - HDMI, MHL, microSD and built in speaker**
- **Built in media play and optional wireless presentations**
- **Compact & Lightweight <0.4kg**



The ML750e ultra-compact portable LED projector is easily transportable between your home and office. This tiny projector weighs less than 0.4kg and comes with a convenient carry bag. Watch HD movies, play video games or even present that winning presentation, the ML750e has everything you need to impress your audience.

Specifications

EAN: 5055387600256, Colour: Black

Display/image

| | |
|--------------------------------|-------------------------------------|
| Display technology | DLP™ |
| Resolution | WXGA (1280x800) |
| Brightness (HK/ANSI) | 700/450 |
| Contrast ratio | 20,000:1 |
| Native aspect ratio | 16:10 |
| Aspect ratio - compatible | 4:3, 16:9 |
| Keystone correction - vertical | +/-40° |
| Horizontal scan rate | 15.375 ~ 91.146Khz |
| Vertical scan rate | 24 ~ 85(120 for 3D)Hz |
| Uniformity | 85% |
| Screen size | 0.43m ~ 2.54m (17" ~ 100") diagonal |

Lamp info

| | |
|-------------------|--------------|
| Light source type | LED |
| LED life | 20,000 hours |

Optical

| | |
|-------------------------|---------------|
| Throw ratio | 1.5:1 |
| Projection distance (m) | 0.55m - 3.23m |
| Zoom type | Fixed |
| Focal length (mm) | 14.95 |
| Native offset | 100% |

Connectivity

| | |
|-------------|---|
| Connections | Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x microSD card, 1 x USB-A reader, 1 x Universal I/O - VGA |
|-------------|---|

General

| | |
|-------------------------|--|
| Noise level (min) | 30dB |
| Noise level (max) | 32dB |
| PC compatibility | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) |
| 3D compatibility | SVGA 120Hz, XGA 120Hz |
| 3D | 3D ready |
| Security | Security bar, Kensington Lock, Password protected interface |
| OSD / display languages | 12 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish |
| Operating conditions | 5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m |
| Remote control | Card style |
| Speaker count | 1 |
| Watts per speaker | 1W |
| In the box | Carry bag Universal I/O cable AC power cord Remote control Battery Basic user manual |

| | |
|--------------------------|---------|
| Input lag | 16.00ms |
| Optional wireless models | WUSB |

Power

| | |
|-----------------------------|-----------------------|
| Power supply | 100 ~ 240V, 50 ~ 60Hz |
| Power consumption (standby) | 0.5W |
| Power consumption (min) | 45W |
| Power consumption (max) | 65W |

Weight and dimensions

| | |
|---------------------------|----------------|
| Dimensions (W x D x H) mm | 105 x 106 x 39 |
| Gross weight | 1.31 kg |
| Net weight | 0.38 kg |

