Technical Specifications

HP E14 G4 Portable Monitor



1. OSD control buttons

2. USB Type C[®] Port



Left

Technical Specifications

HP E14 G4 Portable Monitor



1. Power button

2. USB Type C[®] Port

Right



Technical Specifications

Panel Specifications	Display Size (Diagonal)	14-in
r ance specifications	Panel Technology	IPS
	Refresh Rate	60Hz
	Panel Bit Depth	8-bit
	Aspect Ratio	16:9
	Brightness (Typical)	400 cd/m ²
	Contrast Ratio (Static)	800:1
	Contrast Ratio Minimum (Static)	600:1
	Dynamic Contrast Ratio	5,000,000:1
	Flicker Free	Yes
	Pixel Pitch	0.1611 x 0.1611 mm
	Pixels Per Inch (PPI)	157
	Backlight Lamp Life (to half brightness	15k minimum
	- in hours)	
	Backlight Type	Edge-lit
	Screen Treatment	Anti-glare
	Hardness	3H
	Haze	24%
	Response Time - Typical	5ms GtG (with overdrive)
	Horizontal Viewing Angle (typical	160(min); 178(typ)
	CR>10)	
	Vertical Viewing Angle (typical CR>10)	160(min); 178(typ)
	Panel Active Area (w x h)	309.31 x 173.99 mm
	NOTE: Performance specifications represent the manufacturers; actual performance may vary ei	e typical specifications provided by HP's component ther higher or lower.
Color Gamut Coverage	NTSC	72%
cotor damat coverage	NISC	1270
Monitor Specifications	Bezel	3-sided Micro Edge
-		
-	Bezel	3-sided Micro Edge
-	Bezel Color	3-sided Micro Edge Sliver Stand
-	Bezel Color Height Adjustment Range	3-sided Micro Edge Sliver Stand No height adjust
-	Bezel Color Height Adjustment Range Warranty	3-sided Micro Edge Sliver Stand No height adjust 3/3/0
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified)
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080)
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 1024 @ 60 Hz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported Resolutions	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1680 x 1050 @60Hz 1920 x1080 @60Hz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported Resolutions	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1680 x 1050 @60Hz 1920 x1080 @60Hz 59 Hz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported Resolutions	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1680 x 1050 @60Hz 1920 x1080 @60Hz 59 Hz 60 Hz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported Resolutions	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1680 x 1050 @60Hz 1920 x1080 @60Hz 59 Hz 60 Hz 30.0 kHz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported Resolutions Minimum Vertical Scan Rate Maximum Vertical Scan Rate Minimum Horizontal Scan Rate	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1680 x 1050 @60Hz 1920 x1080 @60Hz 59 Hz 60 Hz 30.0 kHz 80.0 kHz
-	Bezel Color Height Adjustment Range Warranty Low Blue Light Mode Native Resolution ¹ 1. Apply to high resolution and/or high frame ra Maximum Resolution Preset Graphic Modes/Supported Resolutions	3-sided Micro Edge Sliver Stand No height adjust 3/3/0 Yes (TÜV certified) Full HD (1920 x 1080) te displays only. CONFIRM WITH EPM whether disclaimer applies. 1920x1080 60Hz 640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1680 x 1050 @60Hz 1920 x1080 @60Hz 59 Hz 60 Hz 30.0 kHz

Technical Specifications

	IONS			
	User-Assignable Function Buttons Audio Languages	Yes, 4 buttons No Audio 10 (English, Spanish, German Portuguese, Japanese, T-Chir	, French, Italian, Netherlands, 1ese and S-Chinese)	
Connector Types	USB Type-C [®] Video Input	2 USB Type-C [®] with DisplayPe	ort [®] 1.2 Alt mode	
Power & Operating Specs	Power Supply Power Source Power Consumption - Maximum Energy Saving/Standby Mode Power Consumption - Typical Power Passthrough	External (From NB PD Power) PD Power 5v 6 W 0.3 W 3.5 W up to 65 W NOTE: requires external power from		
Operating Conditions	Operating Temperature - Celsius Operating Temperature - Fahrenheit Non-operating Temperature - Celsius Non-operating Temperature - Fahrenheit Operating Humidity Non-operating Humidity Operating Altitude Non-operating Altitude	5 to 35°C 41 to 95°C -20° – 60°C 29° – 140°F 20 – 80% Relative Humidity (non-condensing) 5 – 95% 0 – 5,000 m (16,400 ft.) 0 – 12.192 m (40,000 ft.)		
Environmental Features and Certifications	Mercury-free LED display backlighting Arsenic-Free Display Glass Low Halogen Agency Approvals and Certifications	Yes, Mercury-free LED backlighting Yes Yes WW application CE,CB,KC/KCC/NOM/ICES/TUV-GS/ISO 9241-307/ EAC/UL/cTuvs/ISC/CCC/Energy Star 8/ ISC/VCCI/FCC/BSMI/Vietnam MEPS/WEEE		
	Microsoft WHQL Certification ENERGY STAR® Certified EPEAT® Registered Regions need to verify by country SmartWay Transport Partnership - NA only	/BIS/Cambodia/Taiwan Greer Win 11 Yes Yes Yes (NA sku)	odia/Taiwan Green mark/UAE)	
Plastics	Recyclable Packaging (Box, packing materials)	100% fiber packaging, cardboard		
		<u>Metric</u>	<u>Imperial</u>	
Unit Product/Package Specifications	Product Dimensions (Unpacked with stand) (W x D x H)	32.14 x1.52x 21 cm	12.65X0.60X8.27 in	
	Product Dimensions (Packed) (W x D x H)	40.50 x 6.10 x 28.40 cm	25.43 x 17.24 x 10.59 in	
	Display Head Dimensions (Unpacked without stand) (W x D x H)	53.94 x 32.33 x 4.85 cm	15.94 x 2.40 x 11.18 in	
	Base Area Footprint (w x d mm)	321.37 x 82 mm	12.65 x 3.23 in	
	Bezel Measurements	Top 5.58mm, side 5.58mm, bottom 29.53mm	Top 0.22, side 0.22, bottom 1.16 in	



Technical Specifications

	Product Weight (Unpacked with stand) Product Weight (Packed)	0.64 kg 1.54kg	1.41 lb 3.40 lb
EU Energy Efficiency Class (ERP lot-5)	On-mode Power Consumption	18 W	
	Annual Power Consumption	26 kWh	
	Energy Efficiency Class Visible Screen Size	B 14-inch / 35.56 cm Diagonal	
What's in the box?	Monitor USB Type-C® cable QSP Sleeve		
User Guide and Warranty Languages	User Guide Languages Warranty Languages	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish. English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.	

Summary of Changes

Date of change:	Version History:		Description of change:
February 23, 2021	V1 to V2		Techspecs updated
March 15, 2021	V2 to V3	Added	Power Consumption
December 21, 2023	V3 to V4	Added	Windows 11
	V4 to V5		

Copyright © 2021 HP Development Company, L.P.The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.

